

Litex Membranduk System



1. Unique identification code of product type **ETAG 022-2**
2. Type-, batch- or serial number or any other element allowing identification of the construction product as required under Article 11 (4)
batch number: see packaging label
3. Use intended by the manufacturer or intended use of the construction product according to the applicable harmonised technical specification:

Kits based on flexible sheets

4. Name, registered trade name or registered trade mark and contact address of the manufacturer according to Article 11(5):
**Litex AS
Pindsleveien 4
NO - 3221 Sandefjord**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex 5
System 2+
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
not relevant
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Notified Body Säurefließner-Vereinigung E.V. (No 2012) performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC no.

1212-CPR-1901


9. Declared performance

| Essential characteristics | Performance | Harmonised technical specification |
|------------------------------------|---------------------------|------------------------------------|
| Crack bridging ability | Class 3: 1,5 mm | ETAG 022-2 |
| Bond strength | Class 2: $\geq 0,3$ Mpa | ETAG 022-2 |
| Joint bridging ability | Class 2: watertight | ETAG 022-2 |
| Watertightness around penetrations | Class 2: watertight | ETAG 022-2 |
| Resistance to temperature | temperature-resistant | ETAG 022-2 |
| Resistance to water | Class 2: $\geq 0,3$ Mpa | ETAG 022-2 |
| Resistance to alkalinity | Class 2: alkali-resistant | ETAG 022-2 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sandefjord, 14.01.2020


Øyvind Krohn
Litex AS

